

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : Keno[™]san
 Product code : D41

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial/Professional use spec
 Use of the substance/mixture : See product bulletin for detailed information

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CID LINES NV
 Waterpoortstraat, 2
 B-8900 Ieper - Belgique
 T + 32 57 21 78 77 - F +32 57 21 78 79
sds@cidlines.com - <http://www.cidlines.com>

Importer

Best Veterinary Solutions, Inc
 1716 Detroit St
 P.O. Box 370
 IA 50075 Ellsworth - United States of America
 T 888-378-4045
<https://www.bestvetsolutions.com/>

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	Poisons Information Centre		13 11 26	
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn B -1120 Brussels	+32 70 245 245	
Canada	CANUTEC Country Organization/Company Address Emergency number Comment		(613) 996-6666	
Finland	Poison Information Centre	P.O.B 790 (Tukholmankatu 17) HUS SF - 00029 Helsinki	+358 9 471 977	
Iceland	Eitrunarmiðstöð Landspítali	Fossvogi 108 Reykjavik	+354 543 22 22	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	112	
Netherlands	Nationaal Vergiftigingen Informatie Centrum Uitsluitend bestemd om artsen te informeren bij accidentele vergiftigingen	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	
New Zealand	The National Poisons Centre	University of Otago, 2nd Floor, Adams Building, 18 Frederick Street, 9016 Dunedin	0800 764 766 0800 POISON	
Switzerland	Centre Suisse d'Information Toxicologique Swiss Toxicological Information Centre, Schweizerisches Toxicologisches Informationszentrum STIZ	Freiestrasse 16 Postfach CH-8032 Zurich	+41 44 251 51 51 (International) 145 (National)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

USA	American Association of Poison Control Centers		1-800-222-1222	
-----	---	--	----------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Labelling according to OSHA 29 CFR 1910.1200

Skin corrosion/irritation, Category 1A H314

Serious eye damage/eye irritation, Category 1 H318

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to OSHA 29 CFR 1910.1200

Hazard pictograms (CLP) :



GHS05

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H314 - Causes severe skin burns and eye damage.

Precautionary statements (CLP) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P305 - IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment.
 P363 - Wash contaminated clothing before reuse.
 P301+P330+P331+P310+P321: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Specific treatment.
 P303 - IF ON SKIN (or hair) Remove immediately all contaminated clothing. Wash with plenty of soap and water.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-(2-butoxyethoxy)ethanol	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	5 - 15	Eye Irrit. 2, H319
Sodium hydroxide	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5 (EC Index-No.) 11-002-00-6 (REACH-no) 01-2119457892-27	5 - 15	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Amines, N-C8-22-alkyltrimethylenedi-, acrylated, sodium salts	(CAS-No.) 97659-50-2 (EC-No.) 307-455-7 (REACH-no) Pre-registered	1 - 5	Eye Irrit. 2, H319
Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts	(CAS-No.) 68439-57-6 (EC-No.) 270-407-8 (REACH-no) 01-2119513401-57	1 - 5	Eye Dam. 1, H318 Skin Irrit. 2, H315

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: Assure fresh air breathing. Allow the victim to rest. Seek medical attention immediately.

First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical advice.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Seek medical attention immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting because of corrosive effects. Take to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties. Cough. Sore throat.
Symptoms/effects after skin contact	: Redness, pain. Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	: Redness, pain. Blurred vision. Tears. Serious damage to eyes.
Symptoms/effects after ingestion	: Burning sensation. Cough. Cramps. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

No additional information available

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not combustible.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Corrosive vapours.

5.3. Advice for firefighters

Precautionary measures fire	: Wear fire/flare resistant/retardant clothing. Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flare resistant/retardant clothing. Heat resistant gloves.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak without risks if possible. Collect spillage. Use suitable disposal containers.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: When handling product, avoid contact with skin and eyes. Wear personal protective equipment. Do not breathe vapour/aerosol. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool well ventilated place. Do not store in corrodable metal. Keep container closed when not in use. Protect from freezing.
--------------------	--

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Sodium hydroxide (1310-73-2)**

Austria	MAK (mg/m ³)	2 mg/m ³ (einateerbare Fraktion)
Austria	MAK Short time value (mg/m ³)	4 mg/m ³ max. 8x5 min./Schicht (einateerbare Fraktion) (gemessen als Momentanwert)
Belgium	Local name	Sodium (hydroxyde de) # Natriumhydroxide
Belgium	Limit value (mg/m ³)	2 mg/m ³
Belgium	Remark (BE)	M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkproces moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
Finland	HTP-arvo (15 min)	2 mg/m ³
France	VLE (mg/m ³)	2 mg/m ³
Germany	TRGS 910 Acceptable concentration notes	
Latvia	OEL STEL (mg/m ³)	0.5 mg/m ³
Spain	VLA-EC (mg/m ³)	2 mg/m ³
United Kingdom	Local name	Sodium hydroxide
United Kingdom	WEL STEL (mg/m ³)	2 mg/m ³
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE
Switzerland	MAK (mg/m ³)	2 mg/m ³
Switzerland	KZGW (mg/m ³)	2 mg/m ³
USA - ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³

2-(2-butoxyethoxy)ethanol (112-34-5)

EU	Local name	2-(2-Butoxyethoxy)ethanol
EU	IOELV TWA (mg/m ³)	67.5 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
EU	IOELV STEL (mg/m ³)	101.2 mg/m ³
EU	IOELV STEL (ppm)	15 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium	Local name	2-(2-Butoxyéthoxy)éthanol # 2-(2-Butoxyethoxy)ethanol
Belgium	Limit value (mg/m ³)	67.5 mg/m ³
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m ³)	101.2 mg/m ³
Belgium	Short time value (ppm)	15 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
Germany	TRGS 900 Local name	2-(2-Butoxyethoxy)ethanol
Germany	Occupational exposure limit value (mg/m ³)	67 mg/m ³

2-(2-butoxyethoxy)ethanol (112-34-5)		
Germany	Occupational exposure limit value (ppm)	10 ppm
Germany	Limitation of exposure peaks	1,5(l)
Germany	TRGS 900 Remark	EU;DFG;Y;11
Germany	TRGS 900 Regulatory reference	TRGS900
Germany	TRGS 910 Acceptable concentration notes	
United Kingdom	Local name	2-(2-Butoxyethoxy)ethanol
United Kingdom	WEL TWA (mg/m³)	67.5 mg/m³
United Kingdom	WEL TWA (ppm)	10 ppm
United Kingdom	WEL STEL (mg/m³)	101.2 mg/m³
United Kingdom	WEL STEL (ppm)	15 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE
Norway	Grenseverdier (AN) (mg/m³)	68 mg/m³
Norway	Grenseverdier (AN) (ppm)	10 ppm
Norway	Merknader (NO)	E (EU har en veiledende grenseverdi for stoffet)
Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts (68439-57-6)		
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal	mg/kg bodyweight/day	
Long-term - systemic effects, dermal	2158.33 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	152.22 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects, oral	12.95 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	45.04 mg/m³	
Long-term - systemic effects, dermal	1295 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.024 mg/l Assessment factor: 50	
PNEC aqua (marine water)	0.0024 mg/l Assessment factor: 500	
PNEC aqua (intermittent, freshwater)	0.0197 mg/l Assessment factor: 100	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.767 mg/kg dwt Assessment factor: 1000	
PNEC sediment (marine water)	0.0767 mg/kg dwt Assessment factor: 10000	
PNEC (Soil)		
PNEC soil	1.21 mg/kg dwt Assessment factor: 100	
PNEC (STP)		
PNEC sewage treatment plant	4 mg/l Assessment factor: 10	
Sodium hydroxide (1310-73-2)		
DNEL/DMEL (Workers)		
Long-term - local effects, inhalation	1 mg/m³	
DNEL/DMEL (General population)		
Long-term - local effects, inhalation	1 mg/m³	
2-(2-butoxyethoxy)ethanol (112-34-5)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	101.2 mg/m³	
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day	

Keno™san

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

2-(2-butoxyethoxy)ethanol (112-34-5)	
Long-term - systemic effects, inhalation	67.5 mg/m ³
Long-term - local effects, inhalation	67.5 mg/m ³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	60.7 mg/m ³
Long-term - systemic effects, oral	5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	40.5 mg/m ³
Long-term - systemic effects, dermal	50 mg/kg bodyweight/day
Long-term - local effects, inhalation	40.5 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	1.1 mg/l
PNEC aqua (marine water)	0.11 mg/l
PNEC aqua (intermittent, freshwater)	11 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	4.4 mg/kg dwt
PNEC sediment (marine water)	0.44 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.32 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	56 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	200 mg/l

8.2. Exposure controls

Hand protection:					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)	0.5	2 (< 1.5)	EN ISO 374

Eye protection:			
Type	Use	Characteristics	Standard
Safety glasses, Safety goggles	Droplet	clear, Plastic	EN 166

Skin and body protection:	
Type	Standard
	EN14605:2005+A1:2009

Respiratory protection:			
Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material			
Device	Filter type	Condition	Standard
Full face mask	Filter type A/P2	Long term exposure, Vapour protection	EN 132, EN 140

Personal protective equipment symbol(s):



Other information:

When using do not eat, drink or smoke. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow. brown.
Odour	: No data available
Odour threshold	: No data available
pH	: ≈ 12.5 (1%)
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 1.075 kg/l
Solubility	: Water: 100 %
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

According to process conditions, hazardous decomposition products may be generated.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)

LD50 dermal rabbit	2764 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 2090 - 3645
--------------------	--

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: ≈ 12.5 (1%)
Serious eye damage/irritation	: Causes serious eye damage. pH: ≈ 12.5 (1%)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

Keno™san

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
----------------------------	---

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

2-(2-butoxyethoxy)ethanol (112-34-5)

LC50 fish 1	1300 mg/l Test organisms (species): Lepomis macrochirus
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h algae (1)	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

12.2. Persistence and degradability

Keno™san

Persistence and degradability	The surfactant contained in this preparation complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.
-------------------------------	---

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Dispose in a safe manner in accordance with local/national regulations.
Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point. Hazardous waste due to toxicity. Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: When totally empty, containers are recyclable like any other packing. Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.
European List of Waste (LoW) code	: 07 06 01* - aqueous washing liquids and mother liquors

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: UN 1824
UN-No. (IMDG)	: UN 1824
UN-No. (IATA)	: UN 1824
UN-No. (ADN)	: UN 1824
UN-No. (RID)	: UN 1824

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: SODIUM HYDROXIDE SOLUTION
Proper Shipping Name (IMDG)	: SODIUM HYDROXIDE SOLUTION
Proper Shipping Name (IATA)	: Sodium hydroxide solution
Proper Shipping Name (ADN)	: SODIUM HYDROXIDE SOLUTION
Proper Shipping Name (RID)	: SODIUM HYDROXIDE SOLUTION

Keno™san

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Transport document description (ADR)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III, (E)
Transport document description (IMDG)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III
Transport document description (IATA)	: UN 1824 Sodium hydroxide solution, 8, III
Transport document description (ADN)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III
Transport document description (RID)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 8
Danger labels (ADR)	: 8



IMDG

Transport hazard class(es) (IMDG)	: 8
Danger labels (IMDG)	: 8



IATA

Transport hazard class(es) (IATA)	: 8
Danger labels (IATA)	: 8



ADN

Transport hazard class(es) (ADN)	: 8
Danger labels (ADN)	: 8



RID

Transport hazard class(es) (RID)	: 8
Danger labels (RID)	: 8



14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: III
Packing group (RID)	: III

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No

Keno™san

Safety Data Sheet

According to OSHA 29 CFR 1910.1200


Other information : Clean up even minor leaks or spills, if possible, without unnecessary risk

14.6. Special precautions for user

Special transport precautions : Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, No naked flames, sparks, and do not smoke, Keep public away from danger area, NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY

Overland transport

Classification code (ADR) : C5
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : L4BN
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Hazard identification number (Kemler No.) : 80
Orange plates :



Tunnel restriction code (ADR) : E
EAC code : 2R

Transport by sea

Special provisions (IMDG) : 223
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Stowage category (IMDG) : A
Segregation (IMDG) : SG35
MFAG-No : 153

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 852
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 856
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 8L

Inland waterway transport

Classification code (ADN) : C5
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID)	: C5
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 80

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

California Cleaning Product Right to Know Act of 2017 (SB 258)

Component	CAS-No.	Function	List(s)
Water	7732-18-5	Diluent	Not Applicable
Sodium Hydroxide	1310-73-2	Cleaning Agent	Not Applicable
Butoxydiglycol	112-34-5	Solvent	Not Applicable
Surfactant (amphoteric)	Withheld	Cleaning Agent	Not Applicable
Sodium C14-16 Olefin Sulfonate	68439-57-6	Cleaning Agent	Not Applicable
Amines, C12-14 Alkyldimethyl, N-oxides	308062-28-4	Cleaning Agent	Not Applicable
Surfactant	Withheld	Cleaning Agent	Not Applicable
Surfactant (anionic)	Withheld	Cleaning Agent	Not Applicable
Fatty alcohol	Withheld	Cleaning Agent	Not Applicable
A-Terpinyol-Acetate	80-26-2	Fragrance ingredient	Not Applicable
Terpineol	98-55-5	Fragrance ingredient	Not Applicable
4-Tert-Butylcyclohexyl Acetate	32210-23-4	Fragrance ingredient	Not Applicable

Other information, restriction and prohibition regulations

: Ensure all national/local regulations are observed. PIC Regulation EU (649/2012) - Export and Import of hazardous chemicals. {0} is subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

15.1.2. National regulations

-

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

SDS_U

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.